

KÖSTER Butyl Fix-Tape Fleece

Technical guideline /Article number **10.38**
Issued: October 15, 2009

Cold self-adhesive, fleece-laminated butyl waterproofing tape for upper connections of KÖSTER KSK membranes

Features

KÖSTER Butyl Fix-Tape Fleece is fleece-laminated waterproofing tape on butyl / rubber basis. It is cold self-adhesive, 1.5 mm thick with a separating backing paper on the bottom side. The material can be applied directly from the roll, it is highly tear resistant, immediately waterproof and it can be covered with plaster due to its fleece-laminated upper side. Priming before application of the KÖSTER Butyl Fix-Tape Fleece is not necessary.

Technical data

Material	Butyl / Rubber
Width	15 cm
Thickness	1.5 mm
Temperature resistance	- 25 °C to + 80 °C
Application temperature	+ 5 °C to + 30 °C
μ-value	approx. 135.000
Sd-value	approx. 203

Field of application

KÖSTER Butyl Fix-Tape Fleece is designed for the safe upper connection of KÖSTER KSK membranes on solid, clean, dry, dust- and oil-free substrates.

Application

After waterproofing with KÖSTER KSK membranes, KÖSTER Butyl Fix-Tape Fleece is attached on the upper end of the waterproofing whereby the tape is attached so that half of it covers the membrane and the other half covers the substrate; thus a connection is built which can be plastered. Prior to the application, the protective backing paper on the bottom side of the tape has to be removed.

Due to the laminated fleece on the upper side of the tape, it can be covered with plaster, e. g. in base areas.

Cleaning of tools

Clean soiled sticky cutting tools with KÖSTER Bitumen Remover.

Packaging

10 m roll, width of rolls: 15 cm

Storage

Store the material dry at temperatures between + 5 °C and + 30 °C; it can be stored for approx. 1 year.

Technical guidelines cited

KÖSTER Bitumen Remover	Art. No. 9.03
KÖSTER KSK membranes	Product group 10

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.