

KÖSTER BE Rainproof

Technical guideline / Article number **7.23**
Issued: January 14, 2010

Liquid accelerator for protecting freshly applied products on the basis of bitumen emulsions from rain

Features

KÖSTER BE Rainproof forms a water-resistant film on all fresh bitumen emulsions (KÖSTER Bikuthan® 1C and 2C, KÖSTER Deuxan® Professional and 2C, KÖSTER KBE Liquid Film, KÖSTER Bitumen Emulsion). It reduces the setting time of these coatings and trowel masses. It protects the coatings from rain.

Technical data

| | |
|-------------------------------------|-----------------|
| Active ingredients | inorganic salts |
| Concentration of active ingredients | 12 % |

Field of application

KÖSTER BE Rainproof is used as protection from rain for freshly applied products on the basis of bitumen emulsions.

Application

KÖSTER BE Rainproof is sprayed onto the freshly applied coating using a fine nozzle (e.g. garden spraying device). If the fresh coating is expected to be exposed to a long lasting and heavy rainfall, then protect it additionally with plastic foil.

KÖSTER BE Rainproof must only be applied to the finished waterproofing – it may not be applied to intermediate layers.

Consumption

Approx. 200 g / m²

Cleaning of tools

Clean tools immediately after use with water.

Packaging

5 kg canister

Storage

Store the material cool but frost free; in originally sealed packages, the material can be stored for approx. 2 years.

Safety precautions

Wear protective gloves and goggles when processing the material.

Technical guidelines cited

| | | |
|-----------------------------|----------|-------|
| KÖSTER Bitumen Emulsion | Art.-No. | 1.09 |
| KÖSTER KBE Liquid Film | Art.-No. | 1.13 |
| KÖSTER Bikuthan® 2C | Art.-No. | 1.14 |
| KÖSTER Bikuthan® 1C | Art.-No. | 1.15 |
| KÖSTER Deuxan® 2C | Art.-No. | 1.16 |
| KÖSTER Deuxan® Professional | Art.-No. | 1.161 |

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.