



## KÖSTER BE Rainproof

### Liquid accelerator for protecting freshly applied products on the basis of bitumen emulsions from rain

#### Features

KÖSTER BE Rainproof forms a water-resistant film on all fresh bitumen emulsions (KÖSTER Bikuthan 1C and 2C, KÖSTER Deuxan Professional and 2C, KÖSTER KBE Liquid Film, KÖSTER Bitumen Emulsion). It reduces the setting time of these coatings and trowel masses. It protects the coatings from rain.

#### Technical Data

Active ingredients	Inorganic salts
Concentration of active ingredients	12%

#### Fields of Application

KÖSTER BE Rainproof is used as protection from rain for freshly applied products on the basis of bitumen emulsions.

#### Application

KÖSTER BE Rainproof is sprayed onto the freshly applied coating using a fine nozzle (e.g. garden spraying device). If the fresh coating is expected to be exposed to a long lasting and heavy rainfall protect it additionally with plastic foil.

KÖSTER BE Rainproof must only be applied to the finished waterproofing – it may not be applied to intermediate layers.

#### Consumption

Approx. 0.2 kg/m<sup>2</sup>

#### Cleaning

Clean tools immediately after use with water.

#### Packaging

W 330 005	5 kg jerrycan
-----------	---------------

#### Storage

Store the material cool but frost free. In originally sealed packages the material can be stored for a minimum of 2 years.

#### Safety

Wear protective gloves and goggles when processing the material. Observe all governmental, state, and local safety regulations when processing the material.

#### Related products

KÖSTER Bitumen Emulsion	Prod. code W 190 030
KÖSTER KBE Liquid Film	Prod. code W 245
KÖSTER Bikuthan 2C	Prod. code W 250 028
KÖSTER Bikuthan 1C	Prod. code W 251
KÖSTER Deuxan 2C	Prod. code W 252 032
KÖSTER Deuxan Professional	Prod. code W 256 032

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.